

Cobamat Standard



- Excellent resistance to wear and tear
- Provides comfort underfoot
- Cross-ribbed in both directions for a safer footing in wet or oily conditions
- Fully reversible – easy to clean
- Optional extras: bevelled safety edging (factory fitted) and fixing blocks

Technical Specifications:

- Interwoven PVC matting with open holes (22mm x 22mm)
- Conforms to Slip Resistance Test DIN 51097 Category B
- Resistant to mild acids and alkalis
- Fire tested to DIN 54332 (B2) part of DIN 4102
- Product height: 12mm

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.6 x 10	30	60 x 40	Roll	1	12	Black	CS010610
						Blue	CS020610
0.9 x 10	45	90 x 40	Roll	1	9	Black	CS010910
						Blue	CS020910

Material: PVC extrusions.
 Surface Finish: Cross ribbed lattice effect
 Product Height: 12mm nominal
 Hole Size: 22mm x 22mm
 Operating Temperature: -20^o - +60^oC
 Resistance to Chemicals: PVC is resistant to many different chemicals, alkalis and general industrial chemicals. Please contact the sales office for more specific details.

Environmental Resistance: Suitable for wet and dry areas.
 UV Resistance: Resistant to UV, but please note that red is not colourfast in direct sunlight.

Typical Applications: Ideal for all industrial environments, especially machine tool areas where swarf is in abundance. Conforms to BIA anti-slip test.

Installation Method: Loose lay/reversible
 Accessories: Factory fitted edging where required.
 Fixing cubes to secure mat to the floor.

Cleaning Method: Pressure hose with mild detergent.
 Product Performance: Conforms to the BIA anti slip test and slip resistance test EN 13552 Category R10

Continued on next page

Product Performance:

Fatigue: ● ● ●
Slip Resistance: ● ● ●
Wear: ● ● ●
Low ‡ High ● → ● ● ● ●

Flame Retardancy:

Fire tested to DIN 54332(B2) Part of DIN 4102

Country of Origin:

UK

End of document