

Premier Grip Tiles



- Flexible, hygienic PVC tile
- Provides a slip-resistant surface suitable for leisure environments
- Tiles simply clip together to cover any desired size or shape
- Holes allow drainage of liquids or debris to reduce slipping
- Easy to cut and trim to any shape
- Easily cleaned by hose or pressure washer
- Bevelled edging system available

Technical Specifications:

- Fire tested to EN13501 Euro Classification B(F1)S
- Product height: 13mm

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
.3 x .45	1.3	520 x 310 x 370	Box	0.026	1	Black	PG010001
						Blue	PG020001
Male edge connect					3	Black	
Blk 0.3m 3/pack							
Female edge connect					3	Black	
connect Blk 0.3m 3/pack							
Male edge connect					3	Black	
Blk 0.45m 3/pack							
Fem. edge connect					3	Black	
Blk 0.45m 3/pack							

Product Performance

Slip Resistance Test

DIN 51130: 1992 Testing of floor covering – Determination of slip resistance – Work rooms and areas of work with an increased risk of slipping – Walking method – Ramp test.

Test conducted by a SATRA approved subcontractor under agreement. The test was carried out under UKAS accreditation.

Trial No.	Operator 1 inclined platform shod°	Operator 2 inclined platform shod°
1	18.1	18.9
2	19.5	19.2
3	18.4	19.5
Average	= 18.9°	
Category	= R10	

Continued on next page

Notes: The Premier Grip sample submitted is regarded as suitable for floors in work rooms and work areas where there is an increased risk of slipping due to grease, oil, water, foods, left-overs, dust, flour, plant clippings, etc. It is also suitable for general and private areas when assessed according to DIN 51130.

End of document