

Vyna-Plush



- Economical yet effective scraper doormat
- Slip and stain resistant PVC backing
- Available in 4 attractive colours

Technical Specifications:

- Pile height: 4mm
- Total weight: 2.6 kg/m²
- Pile material is 100% polypropylene
- Product height: 7mm

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.6 x 0.9	2	17.5 x 17.5 x 75	Box	0.02	1	Black/Steel	VP010601
						Black/Red	VP010301
						Black/Blue	VP010201
						Black/Brown	VP010501
0.9 x 1.5	2	17.5 x 17.5 x 105	Box	0.02	1	Black/Steel	VP010602
						Black/Red	VP010302
						Black/Blue	VP010202
						Black/Brown	VP010502
1.2 x 1.8	2	23 x 23 x 124	Box	0.02	1	Black/Steel	VP010603
						Black/Red	VP010303
						Black/Blue	VP010203
						Black/Brown	VP010503

Technical Features:

Manufacturing Process
 Surface Aspect
 Pile material
 Primary Backing
 Machine gauge
 Backing
 Pile Height
 Total Height
 Pile Weight
 Total Weight
 Number of tufts

According to:

ISO 2424 / BS 5557
 ISO 2424 / BS 5557
 DIN 61151 / BS 5557
 ISO 2424
 ISO 1766 / BS 4223 Clause 10
 ISO 1765 / BS 4051
 400 g/m²
 ISO 8543 / BS 4223 Clause 7
 ISO 1763 / BS 4223 Clause 6

Vuilvang
 Cutpile
 100% PA
 Collback TM80
 5/32" COC
 PVC US
 4.0 mm .16 in
 7.0 mm .28 in
 11.8 oz/yd² (+/-7,5%)
 2660 g/m² 78.4 oz/yd² (+/-7,5%)
 65500 1/m² 55000 1/yd²

Continued on next page

Performances:

Walking test	EN 1815 / ISO TR 6356 / DD68	< 2 KV
Dimensional Stability	EN 986 / ISO 2551 / DIN 54318	Voldoet aan de norm(pass)
Electrical resistivity	IBM/ ICL	-
Electrical resistivity vertical	DIN 54345	-
Electrical resistivity horizontal	DIN 54345	-
Sound Insulation	ISO 140-8 / BS 3638	>= 19dB
Thermal retention	ISO 8302 / DIN 52612	-
Soiling (dry / wet)	EN 1289	4.5

Colour fastness:

To light	ISO 105 B02 / DIN 54004/ BS 1006 5
To water	ISO 105 E01 / DIN 54006/ BS 1006 5
To seawater	ISO 105 E02 / DIN 54007/ BS1006 -
To shampoo	BS 1006 5
To rubbing dry	ISO 105 X12/ DIN 54021/BS1006 4
Wet	4

Flammability rating:

NBS Flooring Radiant	ASTM E648/DIN 4102/NEN 1775 -	
Pill (Tablet) test	ISO 6925 = ASTM D2829/ BS 6307 -	
Hot Metal Nut	BS 4790/BS 5287	Low radius
UK Radiant panel test	BS 476 (7) -	
Austrian radiant panel test Oenorm	3810 / Oenorm 3800 (1) -	
Kleinbrenner	DIN 54332 / NEN 1775 (1)	Ta (B2)/T3
Panneau radiant	NF P-92-506 -	

Gut certificate no. 20249

European Overall Classification EN 1307 2LC1

Strapazierwert DIN 66095 (2) Gering Normal Stark Extrem

Komfortwert DIN 66095 (2) Einfach Gut Hoch Luxurious

End of document